

SECTION 1: Identification

1.1. Product identifier

Product form : Mixture
 Product name : 85285B- 8010015831736B (Part B)
 Product code : Finished Good (packaged with part A)
 Product group : 9740-LINE

1.2. Recommended use and restrictions on use

Recommended use : Product for industrial use only
 Restrictions on use : Not applicable

1.3. Supplier

Manufacturer

Tempo Aerospace Inc.
 205 Fenmar Drive
 M9L 2X4 Toronto, ON - Canada
 F 416.746.2235
www.tempo-aerospace.com

Filled by

Delaware Paint Company
 8455 Rausch Drive
 Plain City, Ohio USA 43064
 740-368-9981

1.4. Emergency telephone number

Emergency number : Tempo Aerospace Inc. (416)746-2233; CANUTEC: +01 (613) 996-6666

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Classification (GHS CA)

H226	Flammable liquids, Category 3	Flammable liquid and vapour.
H330	Acute toxicity (inhalation:dust,mist) Category 2	Fatal if inhaled.
H334	Respiratory sensitisation, Category 1	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H317	Skin sensitisation, Category 1	May cause an allergic skin reaction.
H336	Specific target organ toxicity — Single exposure, Category 3, Narcosis	May cause drowsiness or dizziness.

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS CA labelling

Hazard pictograms (GHS CA)



Signal word (GHS CA)

: Danger

Hazard statements (GHS CA)

: H226 - Flammable liquid and vapour.
 H317 - May cause an allergic skin reaction.
 H330 - Fatal if inhaled.
 H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled.
 H336 - May cause drowsiness or dizziness.

Precautionary statements (GHS CA)

: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P233 - Keep container tightly closed.
 P240 - Ground/bond container and receiving equipment.
 P241 - Use explosion-proof electrical/ventilating/lighting equipment.
 P242 - Use only non-sparking tools.
 P243 - Take action to prevent static discharges.
 P260 - Do not breathe dust/fume/gas/mist/vapours/spray.
 P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.
 P271 - Use only outdoors or in a well-ventilated area.
 P272 - Contaminated work clothing should not be allowed out of the workplace.
 P280 - Wear protective gloves/protective clothing/eye protection/face protection.
 P284 - [In case of inadequate ventilation] wear respiratory protection.
 P302+P352 - IF ON SKIN: Wash with plenty of water.

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water .
 P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P310 - Immediately call a POISON CENTER or doctor.
 P312 - Call a POISON CENTER or doctor if you feel unwell.
 P320 - Specific treatment is urgent (see supplemental first aid instruction on this label).
 P321 - Specific treatment (see supplemental first aid instruction on this label)
 P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
 P342+P311 - If experiencing respiratory symptoms: Call a POISON CENTER or doctor.
 P362+P364 - Take off contaminated clothing and wash it before reuse.
 P370+P378 - In case of fire: Use media other than water to extinguish.
 P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
 P403+P235 - Store in a well-ventilated place. Keep cool
 P405 - Store locked up.
 P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS CA)

No data available

SECTION 3: Composition/information on ingredients**3.1. Substances**

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification (GHS CA)
Hexane, 1,6-diisocyanato-, homopolymer	(CAS-No.) 28182-81-2	>= 60*	Acute Tox. 2 (Inhalation:dust,mist), H330
tert-butyl acetate	(CAS-No.) 540-88-5	10 - 30*	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 STOT SE 3, H336 STOT SE 3, H335
n-butyl acetate	(CAS-No.) 123-86-4	5 - 10*	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation:dust,mist), H332 STOT SE 3, H336
1,6-diisocyanatohexane	(CAS-No.) 822-06-0	< 1*	Acute Tox. 4 (Oral), H302 Acute Tox. 2 (Inhalation:dust,mist), H330 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Resp. Sens. 1, H334 Skin Sens. 1, H317 STOT SE 3, H335

Full text of hazard classes and H-statements : see section 16

*Chemical name, CAS number and/or exact concentration have been withheld as CBI

SECTION 4: First-aid measures**4.1. Description of first aid measures**

First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Call a physician immediately. Call a doctor. Call a poison center or a doctor if you feel unwell. If breathing is difficult, trained personnel should give oxygen. Maintain airway. Loosen tight clothing such as a collar, tie, belt or waistband.
First-aid measures after skin contact	: Wash immediately with lots of water (15 minutes)/shower. Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. Get medical advice/attention. Wash clothing before reuse. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical advice/attention.
First-aid measures after ingestion	: Rinse mouth out with water. Remove person to fresh air and keep comfortable for breathing. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. If vomiting occurs have person lean forward. Maintain airway. If unconscious, place in the recovery position and seek medical advice. Call a poison center or a doctor if you feel unwell.
First-aid measures general	: Call a physician immediately. Get medical advice/attention if you feel unwell. Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects	: May cause drowsiness or dizziness.
Symptoms/effects after inhalation	: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Symptoms/effects after skin contact	: May cause an allergic skin reaction.

Durathane FPX Base FS#36081 MIL-PRF- 85285 Type I & IV CL H Polyurethane Topcoat Two-Component Touch-up Paint Pen

Safety Data Sheet

According to the Hazardous Products Regulation (February 11, 2015)

4.3. Immediate medical attention and special treatment, if necessary

Other medical advice or treatment : Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Unsuitable extinguishing media

No additional information available

5.3. Specific hazards arising from the hazardous product

Fire hazard : Flammable liquid and vapour.

Explosion hazard : Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.

5.4. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Evacuate area. Fight fire from safe distance and protected location. Approach fire from upwind to avoid hazardous vapours or gases.

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : No open flames. No smoking.

Personal Precautions, Protective Equipment and Emergency Procedures : Evacuate area. Do not touch or walk on the spilled product. Eliminate ignition sources. Avoid breathing (dust, vapor, mist, gas). Provide adequate ventilation. Wear personal protective equipment.

6.2. Methods and materials for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.

Other information : Dispose of materials or solid residues at an authorized site.

6.3. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection"

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Use only outdoors or in a well-ventilated area. Do not breathe dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.

Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

tert-butyl acetate (540-88-5)		
USA - ACGIH	ACGIH TWA (ppm)	50 ppm
USA - ACGIH	ACGIH STEL (ppm)	150 ppm
USA - ACGIH	Remark (ACGIH)	TLV® Basis: Eye & URT irr
USA - ACGIH	Regulatory reference	ACGIH 2019
USA - OSHA	OSHA PEL (TWA) (mg/m³)	950 mg/m³
USA - OSHA	OSHA PEL (TWA) (ppm)	200 ppm
USA - OSHA	Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1

Durathane FPX Base FS#36081 MIL-PRF- 85285 Type I & IV CL H Polyurethane Topcoat Two-Component Touch-up Paint Pen

Safety Data Sheet

According to the Hazardous Products Regulation (February 11, 2015)

n-butyl acetate (123-86-4)		
USA - ACGIH	ACGIH TWA (ppm)	50 ppm
USA - ACGIH	ACGIH STEL (ppm)	150 ppm
USA - ACGIH	Remark (ACGIH)	TLV® Basis: Eye & URT irr
USA - ACGIH	Regulatory reference	ACGIH 2019
USA - OSHA	OSHA PEL (TWA) (mg/m³)	710 mg/m³
USA - OSHA	OSHA PEL (TWA) (ppm)	150 ppm
USA - OSHA	Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
1,6-diisocyanatohexane (822-06-0)		
USA - ACGIH	ACGIH TWA (ppm)	0.005 ppm
USA - ACGIH	Remark (ACGIH)	TLV® Basis: URT irr; resp sens. Notations: BEI
USA - ACGIH	Regulatory reference	ACGIH 2019

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station. Keep concentrations well below lower explosion limits. Ensure exposure is below occupational exposure limits (where available). Use explosion-proof equipment.

Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Protective gloves

Eye protection:

Safety glasses with side shields

Skin and body protection:

Wear suitable protective clothing. Avoid contact with skin

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. Where exposure through inhalation may occur from use, respiratory protection equipment is recommended

Personal protective equipment symbol(s):



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: No data available
Colour	: Clear
Odour	: acetate
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Relative evaporation rate (ether=1)	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: > 35 °C
Flash point	: ≈ 57 °C (Closed cup)
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapour pressure	: No data available
Vapour pressure at 50 °C	: No data available

Durathane FPX Base FS#36081 MIL-PRF- 85285 Type I & IV CL H Polyurethane Topcoat Two-Component Touch-up Paint Pen

Safety Data Sheet

According to the Hazardous Products Regulation (February 11, 2015)

Relative density	: No data available
Density	: 1.0864 g/cm ³
Solubility	: No data available
Log Pow	: No data available
Explosive limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	: Flammable liquid and vapour.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No dangerous reactions known under normal conditions of use.
Conditions to avoid	: Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Fatal if inhaled.

tert-butyl acetate (540-88-5)	
LD50 oral rat	4500 mg/kg bodyweight (EPA OTS 798.1175, Rat, Male / female, Experimental value, Oral, 014 day(s))
LD50 dermal rabbit	> 2000 mg/kg bodyweight (EPA OTS 798.1100, 24 h, Rabbit, Male / female, Experimental value, Dermal, 14 day(s))
LC50 inhalation rat (ppm)	4211 ppm (6 h, Rat, Male / female, Experimental value, Inhalation (vapours), 14 day(s))

n-butyl acetate (123-86-4)	
LD50 oral rat	10760 - 12789 mg/kg bodyweight (Equivalent or similar to OECD 423, Rat, Male / female, Experimental value, Oral)
LD50 dermal rabbit	14112 mg/kg bodyweight (Equivalent or similar to OECD 402, Rabbit, Male / female, Experimental value, Dermal)
LC50 inhalation rat (mg/l)	1.36 mg/l/4h
LC50 inhalation rat (ppm)	2000 ppm/4h

Hexane, 1,6-diisocyanato-, homopolymer (28182-81-2)	
LD50 oral rat	> 5000 mg/kg OECD 401
LD50 dermal rat	> 5 ml/kg
LD50 dermal rabbit	> 2000 mg/kg EPA 40 CFR 798
LC50 inhalation rat (mg/l)	0.39 mg/l/4h OECD 403, rat-female.

1,6-diisocyanatohexane (822-06-0)	
LD50 oral rat	746 mg/kg (Equivalent or similar to OECD 401, Rat, Male, Experimental value, Oral, 14 day(s))
LD50 dermal rat	> 7000 mg/kg OECD 402
LC50 inhalation rat (mg/l)	0.124 mg/l (OECD 403: Acute Inhalation Toxicity, 4 h, Rat, Male / female, Experimental value, Inhalation (vapours), 28 day(s))
LC50 inhalation rat (ppm)	20 ppm/4h

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitization	: May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified

Reproductive toxicity	: Not classified
-----------------------	------------------

STOT-single exposure	: May cause drowsiness or dizziness.
----------------------	--------------------------------------

Durathane FPX Base FS#36081 MIL-PRF- 85285 Type I & IV CL H Polyurethane Topcoat Two-Component Touch-up Paint Pen

Safety Data Sheet

According to the Hazardous Products Regulation (February 11, 2015)

tert-butyl acetate (540-88-5)	
STOT-single exposure	May cause drowsiness or dizziness. May cause respiratory irritation.
n-butyl acetate (123-86-4)	
STOT-single exposure	May cause drowsiness or dizziness.
1,6-diisocyanatohexane (822-06-0)	
STOT-single exposure	May cause respiratory irritation.
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified
Symptoms/effects	: May cause drowsiness or dizziness.
Symptoms/effects after inhalation	: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Symptoms/effects after skin contact	: May cause an allergic skin reaction.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Not classified

tert-butyl acetate (540-88-5)	
LC50 fish 1	240 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Oncorhynchus mykiss, Semi-static system, Fresh water, Experimental value, GLP)
EC50 Daphnia 1	350 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Locomotor effect)
ErC50 (algae)	16 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)
BCF fish 1	6.734 l/kg (BCFBAF v3.01, Estimated value, Fresh weight)
Log Pow	1.64 (Experimental value, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 21.7 °C)
Log Koc	1.084 - 1.833 (log Koc, SRC PCKOCWIN v2.0, Calculated value)

n-butyl acetate (123-86-4)	
LC50 fish 1	18 mg/l (Equivalent or similar to OECD 203, 96 h, Pimephales promelas, Flow-through system, Fresh water, Experimental value)
EC50 Daphnia 1	44 mg/l (48 h, Daphnia sp., Static system, Fresh water, Experimental value)
EC50 72h algae (1)	674.7 mg/l (Desmodesmus subspicatus, Static system, Fresh water, Experimental value)
BCF fish 1	15.3 (Calculated value)
Log Pow	2.3 (Test data, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 25 °C)
Log Koc	1.268 - 1.844 (log Koc, SRC PCKOCWIN v2.0, QSAR)

1,6-diisocyanatohexane (822-06-0)	
EC50 72h algae (1)	> 77.4 mg/l (EU Method C.3, Desmodesmus subspicatus, Static system, Fresh water, Experimental value, Growth rate)
BCF fish 1	59.6 (BCFWIN, Pisces, QSAR)
Log Pow	3.2 (Calculated)
Log Koc	2.78 - 3.68 (log Koc, Calculated value)

12.2. Persistence and degradability

tert-butyl acetate (540-88-5)	
Persistence and degradability	Not readily biodegradable in water.
n-butyl acetate (123-86-4)	
Persistence and degradability	Readily biodegradable in water.
ThOD	2.21 g O ₂ /g substance
BOD (% of ThOD)	0.46
1,6-diisocyanatohexane (822-06-0)	
Persistence and degradability	Not readily biodegradable in water.

Durathane FPX Base FS#36081 MIL-PRF- 85285 Type I & IV CL H Polyurethane Topcoat Two-Component Touch-up Paint Pen

Safety Data Sheet

According to the Hazardous Products Regulation (February 11, 2015)

12.3. Bioaccumulative potential

tert-butyl acetate (540-88-5)	
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
BCF fish 1	6.734 l/kg (BCFBAF v3.01, Estimated value, Fresh weight)
Log Pow	1.64 (Experimental value, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 21.7 °C)
Log Koc	1.084 - 1.833 (log Koc, SRC PCKOCWIN v2.0, Calculated value)

n-butyl acetate (123-86-4)	
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
BCF fish 1	15.3 (Calculated value)
Log Pow	2.3 (Test data, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 25 °C)
Log Koc	1.268 - 1.844 (log Koc, SRC PCKOCWIN v2.0, QSAR)

1,6-diisocyanatohexane (822-06-0)	
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
BCF fish 1	59.6 (BCFWIN, Pisces, QSAR)
Log Pow	3.2 (Calculated)
Log Koc	2.78 - 3.68 (log Koc, Calculated value)

12.4. Mobility in soil

tert-butyl acetate (540-88-5)	
Surface tension	64 mN/m (20 °C, 1 g/l, OECD 115: Surface Tension of Aqueous Solutions)
Ecology - soil	Highly mobile in soil.
Log Koc	1.084 - 1.833 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Log Pow	1.64 (Experimental value, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 21.7 °C)

n-butyl acetate (123-86-4)	
Surface tension	0.0163 N/m (20 °C)
Ecology - soil	Low potential for adsorption in soil.
Log Koc	1.268 - 1.844 (log Koc, SRC PCKOCWIN v2.0, QSAR)
Log Pow	2.3 (Test data, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 25 °C)

1,6-diisocyanatohexane (822-06-0)	
Ecology - soil	Low potential for mobility in soil.
Log Koc	2.78 - 3.68 (log Koc, Calculated value)
Log Pow	3.2 (Calculated)

12.5. Other adverse effects

Ozone : Not classified

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
Additional information : Flammable vapours may accumulate in the container.

SECTION 14: Transport information

14.1. Basic shipping description

In accordance with TDG

Transportation of Dangerous Goods

UN-No. (TDG) : UN1263
Packing group : III - Minor Danger
TDG Primary Hazard Classes : 3 - Class 3 - Flammable Liquids
Transport document description : UN1263 PAINT RELATED MATERIAL, 3, III
Proper Shipping Name (Transportation of Dangerous Goods) : PAINT RELATED MATERIAL

Durathane FPX Base FS#36081 MIL-PRF- 85285 Type I & IV CL H Polyurethane Topcoat Two-Component Touch-up Paint Pen

Safety Data Sheet

According to the Hazardous Products Regulation (February 11, 2015)

Hazard labels (TDG) : 3 - Flammable liquids



Explosive Limit and Limited Quantity Index : 5 L

Excepted quantities (TDG) : E1

Passenger Carrying Road Vehicle or Passenger : 60 L

Carrying Railway Vehicle Index

14.2. Transport information/DOT

Department of Transport

DOT NA No : UN1263

UN-No.(DOT) : 1263

Packing group (DOT) : III - Minor Danger

Transport document description : UN1263 Paint related material, 3, III

Proper Shipping Name (DOT) : Paint related material

Contains Statement Field Selection (DOT) :

Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

Division (DOT) : 3

Hazard labels (DOT) : 3 - Flammable liquid



Marine pollutant : NO

Emergency Response Guide (ERG) Number : 128

Other information : No supplementary information available.

14.3. Air and sea transport

IMDG

UN-No. (IMDG) : 1263

Proper Shipping Name (IMDG) : PAINT RELATED MATERIAL

Transport document description (IMDG) : UN 1263 PAINT RELATED MATERIAL, 3, III

Class (IMDG) : 3 - Flammable liquids

Packing group (IMDG) : III - substances presenting low danger

IATA

UN-No. (IATA) : 1263

Proper Shipping Name (IATA) : Paint

Transport document description (IATA) : UN 1263 Paint, 3, III

Class (IATA) : 3 - Flammable Liquids

Packing group (IATA) : III - Minor Danger

SECTION 15: Regulatory information

15.1. National regulations

tert-butyl acetate (540-88-5)

Listed on the Canadian DSL (Domestic Substances List)

Canada DSL & NDSL Flags : Substance was manufactured or imported after July 1, 1994

n-butyl acetate (123-86-4)

Listed on the Canadian DSL (Domestic Substances List)

Hexane, 1,6-diisocyanato-, homopolymer (28182-81-2)

Listed on the Canadian DSL (Domestic Substances List)

1,6-diisocyanatohexane (822-06-0)

Listed on the Canadian DSL (Domestic Substances List)

Durathane FPX Base FS#36081 MIL-PRF- 85285 Type I & IV CL H Polyurethane Topcoat Two-Component Touch-up Paint Pen

Safety Data Sheet

According to the Hazardous Products Regulation (February 11, 2015)

15.2. International regulations

tert-butyl acetate (540-88-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

n-butyl acetate (123-86-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Hexane, 1,6-diisocyanato-, homopolymer (28182-81-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

1,6-diisocyanatohexane (822-06-0)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

SECTION 16: Other information

Date of issue : 2019/09/11

Revision date : 2019/09/11

Full text of H-statements:

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.

Tempo SDS GHS Canada

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.