

# Durathane FPX Base FS#36081 MIL-PRF- 85285 Type I & IV CL H Polyurethane Topcoat Two-Component Touch-up Paint Pen

## Safety Data Sheet

According to the Hazardous Products Regulation (February 11, 2015)

Date of issue: 2019/11/25

Revision date: 2019/11/25

Version: 1.0

### SECTION 1: Identification

#### 1.1. Product identifier

Product form : Mixture

Product name : Durathane FPX Base FS#36081 MIL-PRF-85285 Type I & IV CL H Polyurethane Topcoat Two-Component Touch-up Paint Pen

Product code : 8010-01-583-1736 p/n 801085285 (Part A, color 36081)

Product group : 9740-LINE Finished Good

#### 1.2. Recommended use and restrictions on use

Recommended use : Product for industrial use only

Restrictions on use : Not applicable

#### 1.3. Supplier

##### Manufacturer

Tempo Aerospace Inc.  
205 Fenmar Drive  
M9L 2X4 Toronto, ON - Canada  
F 416.746.2235  
[www.tempo-aerospace.com](http://www.tempo-aerospace.com)

##### Filled by

Delaware Paint Company  
8455 Rausch Drive  
Plain City, Ohio USA 43064  
F 740-368-9981

#### 1.4. Emergency telephone number

Emergency number : Tempo Aerospace Inc. (416)746-2233; CANUTEC: +01 (613) 996-6666

### SECTION 2: Hazard identification

#### 2.1. Classification of the substance or mixture

##### Classification (GHS CA)

H226 Flammable liquids, Category 3

Flammable liquid and vapour.

H332 Acute toxicity (inhalation:dust,mist) Category 4

Harmful if inhaled.

H340 Germ cell mutagenicity, Category 1

May cause genetic defects.

H350 Carcinogenicity, Category 1

May cause cancer.

Full text of H statements : see section 16

#### 2.2. GHS Label elements, including precautionary statements

##### GHS CA labelling

Hazard pictograms (GHS CA)



Signal word (GHS CA) : Danger

Hazard statements (GHS CA)

: H226 - Flammable liquid and vapour.  
H332 - Harmful if inhaled.  
H340 - May cause genetic defects.  
H350 - May cause cancer.

Precautionary statements (GHS CA)

: P201 - Obtain special instructions before use.  
P202 - Do not handle until all safety precautions have been read and understood.  
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P233 - Keep container tightly closed.  
P240 - Ground/bond container and receiving equipment.  
P241 - Use explosion-proof electrical/ventilating/lighting equipment.  
P242 - Use only non-sparking tools.  
P243 - Take action to prevent static discharges.  
P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.  
P271 - Use only outdoors or in a well-ventilated area.  
P280 - Wear protective gloves/protective clothing/eye protection/face protection.  
P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.  
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P308+P313 - IF exposed or concerned: Get medical advice/attention.  
P312 - Call a POISON CENTER or doctor if you feel unwell.

# Durathane FPX Base FS#36081 MIL-PRF- 85285 Type I & IV CL H Polyurethane Topcoat Two-Component Touch-up Paint Pen

## Safety Data Sheet

According to the Hazardous Products Regulation (February 11, 2015)

P370+P378 - In case of fire: Use media other than water to extinguish.  
P403+P235 - Store in a well-ventilated place. Keep cool  
P405 - Store locked up.  
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

### 2.3. Other hazards

No additional information available

### 2.4. Unknown acute toxicity (GHS CA)

No data available

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	Classification (GHS CA)
heptan-2-one	(CAS-No.) 110-43-0	10 - 30*	Flam. Liq. 3, H226 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation), H332
tert-butyl acetate	(CAS-No.) 540-88-5	5 - 10*	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 STOT SE 3, H336 STOT SE 3, H335
Titanium oxide, (TiO <sub>2</sub> )	(CAS-No.) 13463-67-7	1 - 10*	Carc. 2, H351
carbon black	(CAS-No.) 1333-86-4	1 - 5*	Carc. 2, H351
solvent naphtha (petroleum), light aromatic	(CAS-No.) 64742-95-6	0.1 - 1*	Flam. Liq. 2, H225 Muta. 1B, H340 Carc. 1B, H350 Asp. Tox. 1, H304

Full text of hazard classes and H-statements : see section 16

\*Chemical name, CAS number and/or exact concentration have been withheld as CBI

## SECTION 4: First-aid measures

### 4.1. Description of first aid measures

First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if you feel unwell. If breathing is difficult, trained personnel should give oxygen. Maintain airway. Loosen tight clothing such as a collar, tie, belt or waistband.
First-aid measures after skin contact	: Wash immediately with lots of water (15 minutes)/shower. Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. Get medical advice/attention. Wash clothing before reuse.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical advice/attention.
First-aid measures after ingestion	: Rinse mouth out with water. Remove person to fresh air and keep comfortable for breathing. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. If vomiting occurs have person lean forward. Maintain airway. If unconscious, place in the recovery position and seek medical advice. Call a poison center or a doctor if you feel unwell.
First-aid measures general	: IF exposed or concerned: Get medical advice/attention. Call a poison center or a doctor if you feel unwell.

### 4.2. Most important symptoms and effects (acute and delayed)

No additional information available

### 4.3. Immediate medical attention and special treatment, if necessary

Other medical advice or treatment : Treat symptomatically.

## SECTION 5: Fire-fighting measures

### 5.1. Suitable extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

### 5.2. Unsuitable extinguishing media

No additional information available

### 5.3. Specific hazards arising from the hazardous product

Fire hazard : Flammable liquid and vapour.

# Durathane FPX Base FS#36081 MIL-PRF- 85285 Type I & IV CL H

## Polyurethane Topcoat Two-Component Touch-up Paint Pen

### Safety Data Sheet

According to the Hazardous Products Regulation (February 11, 2015)

Explosion hazard : Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.

#### 5.4. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Evacuate area. Fight fire from safe distance and protected location. Approach fire from upwind to avoid hazardous vapours or gases.

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : No open flames. No smoking.

Personal Precautions, Protective Equipment and Emergency Procedures : Evacuate area. Do not touch or walk on the spilled product. Eliminate ignition sources. Avoid breathing (dust, vapor, mist, gas). Provide adequate ventilation. Wear personal protective equipment.

#### 6.2. Methods and materials for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.

Other information : Dispose of materials or solid residues at an authorized site.

#### 6.3. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection"

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Limit quantities of product at the minimum necessary for handling and limit the number of exposed workers. Provide local exhaust or general room ventilation. Floors, walls and other surfaces in the hazard area must be cleaned regularly.

Hygiene measures : Separate working clothes from town clothes. Launder separately. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

#### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.

Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

heptan-2-one (110-43-0)		
USA - ACGIH	ACGIH TWA (ppm)	50 ppm
USA - ACGIH	Remark (ACGIH)	TLV® Basis: Eye & skin irr
USA - ACGIH	Regulatory reference	ACGIH 2019
USA - OSHA	OSHA PEL (TWA) (mg/m³)	465 mg/m³
USA - OSHA	OSHA PEL (TWA) (ppm)	100 ppm
USA - OSHA	Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
carbon black (1333-86-4)		
USA - ACGIH	ACGIH TWA (mg/m³)	3 mg/m³ (Inhalable fraction)
USA - ACGIH	Remark (ACGIH)	TLV® Basis: Bronchitis. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
USA - ACGIH	Regulatory reference	ACGIH 2019
USA - OSHA	OSHA PEL (TWA) (mg/m³)	3.5 mg/m³
USA - OSHA	Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1

# Durathane FPX Base FS#36081 MIL-PRF- 85285 Type I & IV CL H

## Polyurethane Topcoat Two-Component Touch-up Paint Pen

### Safety Data Sheet

According to the Hazardous Products Regulation (February 11, 2015)

tert-butyl acetate (540-88-5)		
USA - ACGIH	ACGIH TWA (ppm)	50 ppm
USA - ACGIH	ACGIH STEL (ppm)	150 ppm
USA - ACGIH	Remark (ACGIH)	TLV® Basis: Eye & URT irr
USA - ACGIH	Regulatory reference	ACGIH 2019
USA - OSHA	OSHA PEL (TWA) (mg/m³)	950 mg/m³
USA - OSHA	OSHA PEL (TWA) (ppm)	200 ppm
USA - OSHA	Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
Titanium oxide, (TiO2) (13463-67-7)		
USA - ACGIH	ACGIH TWA (mg/m³)	10 mg/m³
USA - ACGIH	Remark (ACGIH)	TLV® Basis: LRT irr. Notations: A4 (Not classifiable as a Human Carcinogen)
USA - ACGIH	Regulatory reference	ACGIH 2019
USA - OSHA	OSHA PEL (TWA) (mg/m³)	15 mg/m³
USA - OSHA	Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1

#### 8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station. Keep concentrations well below lower explosion limits. Ensure exposure is below occupational exposure limits (where available). Use explosion-proof equipment.

Environmental exposure controls : Avoid release to the environment.

#### 8.3. Individual protection measures/Personal protective equipment

##### Hand protection:

Protective gloves

##### Eye protection:

Safety glasses with side shields

##### Skin and body protection:

Wear suitable protective clothing. Avoid contact with skin

##### Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. Where exposure through inhalation may occur from use, respiratory protection equipment is recommended

#### Personal protective equipment symbol(s):



## SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state : Liquid

Appearance : No data available

Colour : Grey

Odour : ketones

Odour threshold : No data available

pH : No data available

Relative evaporation rate (butylacetate=1) : No data available

Relative evaporation rate (ether=1) : No data available

Melting point : Not applicable

Freezing point : No data available

Boiling point : > 35 °C

Flash point : ≈ 27 °C

Auto-ignition temperature : No data available

# Durathane FPX Base FS#36081 MIL-PRF- 85285 Type I & IV CL H Polyurethane Topcoat Two-Component Touch-up Paint Pen

## Safety Data Sheet

According to the Hazardous Products Regulation (February 11, 2015)

Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapour pressure	: No data available
Vapour pressure at 50 °C	: No data available
Relative density	: No data available
Density	: 1.1031 g/cm <sup>3</sup>
Solubility	: No data available
Log Pow	: No data available
Explosive limits	: No data available

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Reactivity	: Flammable liquid and vapour.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No dangerous reactions known under normal conditions of use.
Conditions to avoid	: Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Harmful if inhaled.

<b>heptan-2-one (110-43-0)</b>	
LD50 oral rat	1600 mg/kg bodyweight (Rat, Experimental value, Oral, 14 day(s))
LD50 dermal rat	> 2000 mg/kg bodyweight (OECD 402: Acute Dermal Toxicity, 24 h, Rat, Male / female, Experimental value, Dermal)
LD50 dermal rabbit	10313 mg/kg
LC50 inhalation rat (mg/l)	> 16.7 mg/l air (OECD 403: Acute Inhalation Toxicity, 4 h, Rat, Male / female, Experimental value, Inhalation (vapours), 14 day(s))

<b>carbon black (1333-86-4)</b>	
LD50 oral rat	> 8000 mg/kg (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral)
LD50 dermal rabbit	> 3000 mg/kg (Rabbit, Literature study, Dermal)
LC50 inhalation rat (mg/l)	> 4.6 mg/l air (4 h, Rat, Experimental value, Inhalation)

<b>solvent naphtha (petroleum), light aromatic (64742-95-6)</b>	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat (ppm)	3670 ppm/4h

<b>tert-butyl acetate (540-88-5)</b>	
LD50 oral rat	4500 mg/kg bodyweight (EPA OTS 798.1175, Rat, Male / female, Experimental value, Oral, 014 day(s))
LD50 dermal rabbit	> 2000 mg/kg bodyweight (EPA OTS 798.1100, 24 h, Rabbit, Male / female, Experimental value, Dermal, 14 day(s))
LC50 inhalation rat (ppm)	4211 ppm (6 h, Rat, Male / female, Experimental value, Inhalation (vapours), 14 day(s))

<b>Titanium oxide, (TiO2) (13463-67-7)</b>	
LD50 oral rat	> 5000 mg/kg bodyweight (OECD 425: Acute Oral Toxicity: Up-and-Down Procedure, Rat, Female, Experimental value, Oral, 14 day(s))
LC50 inhalation rat (mg/l)	> 6.82 mg/l (Other, 4 h, Rat, Male, Experimental value, Inhalation (dust), 14 day(s))
LC50 inhalation rat (Dust/Mist - mg/l/4h)	> 6.82 mg/l/4h Dust

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitization	: Not classified

# Durathane FPX Base FS#36081 MIL-PRF- 85285 Type I & IV CL H Polyurethane Topcoat Two-Component Touch-up Paint Pen

## Safety Data Sheet

According to the Hazardous Products Regulation (February 11, 2015)

Germ cell mutagenicity : May cause genetic defects.  
Carcinogenicity : May cause cancer.

Reproductive toxicity : Not classified

STOT-single exposure : Not classified

<b>tert-butyl acetate (540-88-5)</b>	
STOT-single exposure	May cause drowsiness or dizziness. May cause respiratory irritation.

STOT-repeated exposure : Not classified

Aspiration hazard : Not classified

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.  
Hazardous to the aquatic environment, short-term (acute) : Not classified  
Hazardous to the aquatic environment, long-term (chronic) : Not classified

<b>heptan-2-one (110-43-0)</b>	
LC50 fish 1	131 mg/l (EPA OPP 72-1, 96 h, Pimephales promelas, Flow-through system, Fresh water, Experimental value, Lethal)
EC50 Daphnia 1	> 90.1 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Semi-static system, Fresh water, Experimental value, GLP)
EC50 72h algae (1)	98.2 mg/l (OECD 201: Alga, Growth Inhibition Test, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Growth rate)
EC50 72h algae (2)	75.5 mg/l (OECD 201: Alga, Growth Inhibition Test, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Biomass)
Log Koc	1.45 (log Koc, EU Method C.19, Experimental value)

<b>carbon black (1333-86-4)</b>	
LC50 fish 1	> 1000 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Brachydanio rerio, Literature study)
EC50 Daphnia 1	> 5600 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 24 h, Daphnia magna, Static system, Fresh water, Experimental value)
EC50 72h algae (1)	> 10000 mg/l (OECD 201: Alga, Growth Inhibition Test, Scenedesmus subspicatus, Static system, Fresh water, Experimental value)

<b>solvent naphtha (petroleum), light aromatic (64742-95-6)</b>	
Log Pow	2.1 - 6

<b>tert-butyl acetate (540-88-5)</b>	
LC50 fish 1	240 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Oncorhynchus mykiss, Semi-static system, Fresh water, Experimental value, GLP)
EC50 Daphnia 1	350 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Locomotor effect)
ErC50 (algae)	16 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)
BCF fish 1	6.734 l/kg (BCFBAF v3.01, Estimated value, Fresh weight)
Log Pow	1.64 (Experimental value, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 21.7 °C)
Log Koc	1.084 - 1.833 (log Koc, SRC PCKOCWIN v2.0, Calculated value)

<b>Titanium oxide, (TiO2) (13463-67-7)</b>	
LC50 fish 1	> 100 mg/l (Equivalent or similar to OECD 203, 96 h, Oncorhynchus mykiss, Static system, Fresh water, Experimental value, Nominal concentration)
ErC50 (algae)	61 mg/l (EPA 600/9-78-018, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Nominal concentration)

### 12.2. Persistence and degradability

# Durathane FPX Base FS#36081 MIL-PRF- 85285 Type I & IV CL H Polyurethane Topcoat Two-Component Touch-up Paint Pen

## Safety Data Sheet

According to the Hazardous Products Regulation (February 11, 2015)

<b>heptan-2-one (110-43-0)</b>	
Persistence and degradability	Readily biodegradable in water.
BOD (% of ThOD)	0.44
<b>carbon black (1333-86-4)</b>	
Persistence and degradability	Biodegradability in soil: not applicable. Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable
<b>tert-butyl acetate (540-88-5)</b>	
Persistence and degradability	Not readily biodegradable in water.
<b>Titanium oxide, (TiO<sub>2</sub>) (13463-67-7)</b>	
Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable (inorganic)
ThOD	Not applicable (inorganic)

### 12.3. Bioaccumulative potential

<b>heptan-2-one (110-43-0)</b>	
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
Log Koc	1.45 (log Koc, EU Method C.19, Experimental value)
<b>carbon black (1333-86-4)</b>	
Bioaccumulative potential	Not bioaccumulative.
<b>solvent naphtha (petroleum), light aromatic (64742-95-6)</b>	
Log Pow	2.1 - 6
<b>tert-butyl acetate (540-88-5)</b>	
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
BCF fish 1	6.734 l/kg (BCFBAF v3.01, Estimated value, Fresh weight)
Log Pow	1.64 (Experimental value, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 21.7 °C)
Log Koc	1.084 - 1.833 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
<b>Titanium oxide, (TiO<sub>2</sub>) (13463-67-7)</b>	
Bioaccumulative potential	Not bioaccumulative.

### 12.4. Mobility in soil

<b>heptan-2-one (110-43-0)</b>	
Surface tension	0.0591 N/m (21.6 °C, EU Method A.5: Surface tension)
Ecology - soil	Highly mobile in soil.
Log Koc	1.45 (log Koc, EU Method C.19, Experimental value)
<b>carbon black (1333-86-4)</b>	
Ecology - soil	Adsorbs into the soil. Not toxic to plants. Not toxic to animals.
<b>solvent naphtha (petroleum), light aromatic (64742-95-6)</b>	
Log Pow	2.1 - 6
<b>tert-butyl acetate (540-88-5)</b>	
Surface tension	64 mN/m (20 °C, 1 g/l, OECD 115: Surface Tension of Aqueous Solutions)
Ecology - soil	Highly mobile in soil.
Log Koc	1.084 - 1.833 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Log Pow	1.64 (Experimental value, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 21.7 °C)
<b>Titanium oxide, (TiO<sub>2</sub>) (13463-67-7)</b>	
Ecology - soil	Low potential for mobility in soil.

### 12.5. Other adverse effects

Ozone : Not classified



# Durathane FPX Base FS#36081 MIL-PRF- 85285 Type I & IV CL H Polyurethane Topcoat Two-Component Touch-up Paint Pen

## Safety Data Sheet

According to the Hazardous Products Regulation (February 11, 2015)

### SECTION 13: Disposal considerations

#### 13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.  
Additional information : Flammable vapours may accumulate in the container.

### SECTION 14: Transport information

#### 14.1. Basic shipping description

In accordance with TDG

#### Transportation of Dangerous Goods

UN-No. (TDG) : UN1263  
Packing group : III - Minor Danger  
TDG Primary Hazard Classes : 3 - Class 3 - Flammable Liquids  
Transport document description : UN1263 PAINT, 3, III  
Proper Shipping Name (Transportation of Dangerous Goods) : PAINT  
  
Hazard labels (TDG) : 3 - Flammable liquids



Explosive Limit and Limited Quantity Index : 5 L  
Excepted quantities (TDG) : E1  
Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index : 60 L

#### 14.2. Transport information/DOT

#### Department of Transport

DOT NA No : UN1263  
UN-No.(DOT) : 1263  
Packing group (DOT) : III - Minor Danger  
Transport document description : UN1263 Paint, 3, III  
Proper Shipping Name (DOT) : Paint  
Contains Statement Field Selection (DOT) :  
Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120  
Division (DOT) : 3  
Hazard labels (DOT) : 3 - Flammable liquid



Marine pollutant : NO  
Emergency Response Guide (ERG) Number : 128  
Other information : No supplementary information available.

#### 14.3. Air and sea transport

#### IMDG

UN-No. (IMDG) : 1263  
Proper Shipping Name (IMDG) : PAINT  
Transport document description (IMDG) : UN 1263 PAINT, 3, III  
Class (IMDG) : 3 - Flammable liquids  
Packing group (IMDG) : III - substances presenting low danger

#### IATA

UN-No. (IATA) : 1263



# Durathane FPX Base FS#36081 MIL-PRF- 85285 Type I & IV CL H Polyurethane Topcoat Two-Component Touch-up Paint Pen

## Safety Data Sheet

According to the Hazardous Products Regulation (February 11, 2015)

Proper Shipping Name (IATA)	: Paint
Transport document description (IATA)	: UN 1263 Paint, 3, III
Class (IATA)	: 3 - Flammable Liquids
Packing group (IATA)	: III - Minor Danger

### SECTION 15: Regulatory information

#### 15.1. National regulations

<b>heptan-2-one (110-43-0)</b>	
Listed on the Canadian DSL (Domestic Substances List)	
<b>carbon black (1333-86-4)</b>	
Listed on the Canadian DSL (Domestic Substances List)	
<b>solvent naphtha (petroleum), light aromatic (64742-95-6)</b>	
Listed on the Canadian DSL (Domestic Substances List)	
<b>tert-butyl acetate (540-88-5)</b>	
Listed on the Canadian DSL (Domestic Substances List)	
Canada DSL & NDSL Flags	Substance was manufactured or imported after July 1, 1994
<b>Titanium oxide, (TiO<sub>2</sub>) (13463-67-7)</b>	
Listed on the Canadian DSL (Domestic Substances List)	

#### 15.2. International regulations

<b>heptan-2-one (110-43-0)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>carbon black (1333-86-4)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>solvent naphtha (petroleum), light aromatic (64742-95-6)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>tert-butyl acetate (540-88-5)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>Titanium oxide, (TiO<sub>2</sub>) (13463-67-7)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	

### SECTION 16: Other information

Date of issue	: 2019/10/21
Revision date	: 2019/10/21

Full text of H-statements:

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H340	May cause genetic defects.
H350	May cause cancer.
H351	Suspected of causing cancer.

Tempo SDS GHS Canada

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.*