Randolph Products Company

MIL-PRF-85285E 24052 TYPE 1 AND 2 CLASS H - POLYURETHANE TOPCOAT TWO COMPONENT TOUCH-UP PEN

Date Printed: 11/6/2019

Page 1 of 18

1. Product and Company Identification

Product Name: MIL-PRF-85285E 24052 TYPE 1 AND 2 CLASS H-POLYURETHANE TOPCOAT TWO COMPONENT TOUCH-UP PEN

Product Code: 8010-01-441-6006 p/n 801085285 (Part A, color 24052)

Recommended Use: Please refer to Product Information/Technical Data Sheet.

Company Identification:

Randolph Products Company 33 Haynes Circle Chicopee, MA 01020

Information Phone: 413-592-4191

Emergency Phone: ChemTel 800-255-3924

Product filled by:
Delaware Paint Company
8455 Rausch Drive
Plain City, Ohio 43064
740-368-9981

2. Hazards Identification

EMERGENCY OVERVIEW

HAZARD CLASSIFICATION:

HIGHLY FLAMMABLE LIQUID & VAPOR, CATEGORY 2

ACUTE TOXICITY (ORAL), CATEGORY 4

SKIN IRRITATION, CATEGORY 2

EYE IRRITATION, CATEGORY 2B

SPECIFIC TARGET ORGAN TOXICITY-SINGLE EXPOSURE, CATEGORY 3 (CENTRAL NERVOUS

SYSTEM)

ASPIRATION HAZARD, CATEGORY 1

CARCINOGENICITY, CATEGORY 1

SIGNAL WORD:

DANGER







SAFETY DATA SHEET Randolph Products Company MIL-PRF-85285E 24052 TYPE 1 AND 2 CLASS H - POLYURETHANE TOPCOAT TWO COMPONENT TOUCH-UP PEN Date Printed: 11/6/2019 Page 2 of 18 HAZARD STATEMENTS: HIGHLY FLAMMABLE LIQUID AND VAPOR HARMFUL IF SWALLOWED CAUSES SKIN IRRITATION CAUSES EYE IRRITATION MAY CAUSE DROWSINESS OR DIZZINESS MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS MAY CAUSE CANCER PRECAUTIONARY STATEMENTS: Keep away from heat, sparks, open flame/hot surfaces. No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting and other equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Store/Use in a well ventilated place. Keep cool. Store locked up. Wash hands thoroughly after handling. Do not eat or drink while using this product. Do not breathe vapors. If inhaled: Remove person to fresh air and keep comfortable for breathing. If swallowed, immediately call a poison control center. Rinse mouth. Wear protective gloves, protective clothing, eye/face protection. If on skin, wash with plenty of water. If skin irritation occurs, seek medical advice. Take off contaminated clothing and wash it before reuse. If in eyes, rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: get medical attention. Do NOT induce vomiting.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Potential Health Effects Can cause eye irritation. Skin: Causes skin irritation.

Ingestion:

If swallowed, call a poison control center or physician if you feel unwell. Rinse mouth.

Inhalation:

May cause drowsiness or dizziness.

Randolph Products Company

MIL-PRF-85285E 24052 TYPE 1 AND 2 CLASS H - POLYURETHANE TOPCOAT TWO COMPONENT TOUCH-UP PEN Date Printed: 11/6/2019

Page 3 of 18

Chronic (Cancer) Information:

Contains CRYSTALLINE SILICA, which can be a health hazard. Respirable crystalline silica can cause the occupational

lung disease silicosis (a scarring of the lungs), and IARC concluded in October 1996 that crystalline silica is

carcinogenic to humans. Silicosis increases the risk of tuberulosis, autoimmune and chronic kidney diseases, as well as

non-malignant respiratory disease (such as chronic bronchitis and emphysema).

Contains CARBON BLACK, which is listed by

the IARC as a Group 2B (possibly carcinogenic to humans). Not listed as a carcinogen by NTP, ACGIH, OSHA or the

European Union. There are no known human carcinogenic effects related to the PAH content in carbon blacks. Recent

research has shown that the PAH content of carbon blacks is not released in biological fluids and thus not available for biological activity.

IARC: A component of this product present at levels greater than or equal to 0.1% is identified as a probable, possible or confirmed human carcinogen by IARC.

ACGIH: A component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

NTP: A component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Teratology (Birth Defects) Information:

INFORMATION NOT AVAILABLE.

Reproduction Information:

INFORMATION NOT AVAILABLE.

Aggravation of Pre-Existing Conditions:

Dermititis or other skin conditions.

3. Composition/Information on Ingredients

Component	CAS#	% by Wt.
# MICROCRYSTALLINE SILICA (QUARTZ) ACGIH: 10 MG/M3 TWA, TOTAL DUST	14808-60-7	13.7
OSHA: 20 MPPCF3 TWA BARIUM SULFATE	7727-43-7	12
ACGIH: 10 MG/M3 TWA OSHA: 15 MG/M3 TWA		
TALC	14807-96-6	10

Randolph Products Company

MIL-PRF-85285E 24052 TYPE 1 AND 2 CLASS H - POLYURETHANE TOPCOAT TWO COMPONENT TOUCH-UP PEN

Date Printed: 11/6/2019

Page 4 of 18		
ACGIH TLV: 2 MG/M3 TWA, RESPIRABLE DUST		
OSHA PEL: 20 MPPCF TWA		
N-BUTYL ACETATE	123-86-4	6
ACGIH: 150 PPM TWA		
OSHA: 150 PPM TWA		
ACGIH: 200 PPM STEL		
OSHA: 200 PPM CEILING		
PROPYLENE GLYCOL MONOMETHYL ETHER ACETATE	108-65-6	4
SUPPLIER RECOMMENDED: 30 PPM TWA		
*+# METHYL ISOBUTYL KETONE	108-10-1	4.1
ACGIH TLV: 50 PPM TWA		
ACGIH TLV: 75 PPM STEL		
OSHA PEL: 100 PPM TWA		
METHYL NORMAL AMYL KETONE	110-43-0	4
OSHA PEL 100 PPM - TWA		
OSHA VPEL 100 PPM -TWA		
ACGIH TLV 50 PPM - TWA		
ACGIH TLV 233 MG/M3 - TWA		
DIISOBUTYL KETONE	108-83-8	3
ACGIH TLV: 25 PPM TWA		
OSHA PEL: 50 PPM TWA		
OSHA VPEL: 25 PPM TWA		
METHYL ETHYL KETONE	78-93-3	3
ACGIH: 200 PPM TWA		
OSHA: 200 PPM TWA		
MODIFIED OXAZOLIDINE	145899-78-1	2
NOT ESTABLISHED		
HYDRATED AMORPHOUS SILICA	112926-00-8	2
ACGIH: 10 MG/M3 TWA, TOTAL DUST		
OSHA: 6 MG/M3 TWA		
LT YELLOW IRON OXIDE	51274-00-1	2
ACGIH: 5 MG/M3 TWA (FUMES)		
OSHA: 10 MG/M3 TWA (FUMES)		
TERTIARY BUTYL ACETATE	540-88-5	1
ACGIH: 200 PPM TWA		
OSHA: 200 PPM TWA		
# TITANIUM DIOXIDE	13463-67-7	1.012
ACGIH: 10 MG/M3 TWA - NUISANCE DUST		
OSHA: 10 MG/M3 TWA - NUISANCE DUST	100 54 6	4
2,4-PENTANEDIONE	123-54-6	1
EXPOSURE LIMITS: NOT ESTABLISHED	C4740 OF C	1
SOLVENT NAPHTHA (PETROLEUM), LIGHT AROMATIC	64/42-95-6	1
OSHA PEL: 500 PPM (2000 MG/M3)		
ACGIH TLV: 200 MG/M3 (AS TOTAL HYDROCARBON VAPOR) # CARBON BLACK	1333-86-4	2 / 1
ACGIH: 3.5 MG/M3 TWA	1333-00-4	.341
OSHA: 3.5 MG/M3 TWA		
# ETHYL BENZENE	100-41-4	0.8.0
ACGIH TLV 100 PPM - TWA	TOO 4T 4	• 0 0 0
OSHA PEL 100 PPM - TWA		
ODIM THE TOO ITH TWA		

Randolph Products Company

MIL-PRF-85285E 24052 TYPE 1 AND 2 CLASS H - POLYURETHANE TOPCOAT TWO COMPONENT TOUCH-UP PEN Date Printed: 11/6/2019

Page 5 of 18

OSHA PEL 100 PPM - TWA OSHA PEL 125 PPM - CEILING

4. First Aid Measures

Eyes:

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

Skin:

If on skin: wash with plenty of soap & water. If skin irritation occurs: Get Medical advice/attention.

Take off contaminated clothing and wash it before reuse.

Ingestion:

If swallowed: Immediately call a poison center/physician. Do NOT induce vomiting.

Inhalation:

If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison control center/get medical attention if you feel unwell.

Note to Physicians:

Aspiration hazard - do not induce vomiting

5. Fire Fighting Measures

Flammable Properties:

Flash Point: 20 F Method:

Explosive Limits:

Lower explosive limit: 0.8
Upper explosive limit: 11.4

Autoignition Temperature:

INFORMATION NOT AVAILABLE.

Hazardous Combustion Products:

Smoke, soot and carbon dioxide, carbon monoxide.

Extinguishing Media:

Dry chemical, CO2, Halon, Foam

Firefighting Procedures:

Special Fire-Fighting Procedures: Wear self-contained breathing apparatus and protective clothing.

proceedive erodiring.

Unusual Fire and Explosion Hazards: High temperatures can cause sealed containers to rupture due to a build up of

Randolph Products Company

MIL-PRF-85285E 24052 TYPE 1 AND 2 CLASS H - POLYURETHANE TOPCOAT TWO COMPONENT TOUCH-UP PEN Date Printed: 11/6/2019

Page 6 of 18

internal pressure. Cool with water spray. Vapors are heavier than air and can travel some distance away and flash back.

Sensitivity to Static Discharge: Material may accumulate a static charge which could act as an ignition source.

Precautions should be taken when pouring to minimize splash/free fall.

6. Accidental Release Measures

Small Spill:

See Information for Large Spill, below:

Large Spill:

Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to

safe areas. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.

Environmental Precautions:

INFORMATION NOT AVAILABLE.

Methods/Materials for Containment and Cleaning Up:

Contain spillage, and then collect with non-combustible absorbent material,

(e.g. sand earth, diatomaceous earth,

vermiculite) and place in container for disposal according to

local/state/federal regulations.

7. Handling and Storage

Handling:

Keep away from heat, sparks, open flames, hot surfaces. NO SMOKING. Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/processing equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Wear protective gloves/eye protection/face protection.

Storage:

Prevent unauthorized access.

Store in a well ventilated place.

Keep container tightly closed.

Keep cool.

8. Exposure Controls/Personal Protection

Airborne Exposure Limits: SEE SECTION 3 FOR THIS INFORMATION

Randolph Products Company

MIL-PRF-85285E 24052 TYPE 1 AND 2 CLASS H - POLYURETHANE TOPCOAT TWO COMPONENT TOUCH-UP PEN Date Printed: 11/6/2019

Page 7 of 18

Engineering Controls:

Ventilation: Good general ventilation (typically 10 air changes per hour)

should be used.

Ventilation rates should be matched to conditions.

Ventilation should be explosion proof.

Supplementary local exhaust ventilation, closed systems, or respiratory

protection may be needed in special

circumstances such as poorly ventilated spaces, spray painting, mechanical

generation of dusts, heating, drying, etc.

Personal Protective Equipment

Respiratory Protection:

If engineering controls do not maintain airborne concentrations to an acceptable level, an approved respirator must be

worn. In the United States of America, if respirators are used, a program should be instituted to assure compliance

with OSHA Standard 63 CFR 1152, January 8, 1998. Respirator type: Organic Vapor.

Skin Protection:

Wear impervious gloves to prevent skin contact.

Recommended Decontamination Facilities: eye bath, washing facilities, safety shower.

Eye Protection:

Chemical safety goggles or glasses with side shields.

9. Physical and Chemical Properties

Boiling Point: 175 F

Melting Point:

INFORMATION NOT AVAILABLE.

Freezing Point: -63F

Vapor Pressure:

Information not available for mixture

Vapor Density:

HEAVIER THAN AIR

Solubility in Water:

NEGLIGIBLE

Evaporation Rate: SLOWER THAN ETHER

Specific Gravity: 1.373

Weight per Gallon: 11.436 lb/gl

Coating VOC: 3.07 lb/gl

Randolph Products Company

MIL-PRF-85285E 24052 TYPE 1 AND 2 CLASS H - POLYURETHANE TOPCOAT TWO COMPONENT TOUCH-UP PEN

Page 8 of 18

Material VOC: 3.01 lb/gl

Date Printed: 11/6/2019

Odor:

Mild solvent odor.

Appearance:

Liquid.

Partition Coefficient: INFORMATION NOT AVAILABLE.

10. Stability and Reactivity

Chemical Stability (Conditions to Avoid):
Stable under normal storage/use conditions.
Incompatibility:
Avoid strong oxidizing agents, acids and alkalies.
Hazardous Decomposition Products:
INFORMATION NOT AVAILABLE.
Hazardous Polymerization:
Will not occur under normal conditions.

11. Toxicological Information

Eye Irritation/Damage:
Component 100-41-4:
Mild eye irritation, Category 2b

Component 64742-95-6:
Mild eye irritation, Category 2b
Component 78-93-3:
Mild eye irritation, Category 2B
Component 540-88-5:
Based on available data, the classification criteria are not met.

Skin Irritation/Damage:
Component 100-41-4:
LD50: >2000 mg/kg, rat. Category 5

Component 64742-95-6:
LD50: >2000 mg/kg, rat. Category 5

Component 78-93-3:
Moderate skin irritation, Category 2
LD50: >5000 mg/kg, rabbit
Component 540-88-5:
LD50: >2000 mg/kg, rabbit. Category 5.

Randolph Products Company

MIL-PRF-85285E 24052 TYPE 1 AND 2 CLASS H - POLYURETHANE TOPCOAT TWO COMPONENT TOUCH-UP PEN
Date Printed: 11/6/2019

Page 9 of 18

Acute Oral Toxicity:
Component 100-41-4:
LD50: >2000 mg/kg, rat. Category 5.

Component 1333-86-4:
LD50: >8000 mg/kg, rat. Category 5
Component 13463-67-7:
LD50: 10,000 mg/kg, rat. Category 5

Component 108-10-1: LD50: 2080 mg/kg, rat. Category 4 Component 78-93-3: LD50: 2300-3500 mg/kg, rat. Category 5 Component 123-86-4: LD50: 10,700 mg/kg, rat. Category 5 Component 540-88-5: LD50: 4,500 mg/kg, rat. Category 5 Component 108-65-6: LD50: no data Acute Inhalation Toxicity: Component 100-41-4: LC50: 2-20 mg/l, rat. Category 3 Component 64742-95-6: LC50: 5.6 mg/l, rat. Category 3 Component 78-93-3: LD50: 11,700 mg/kg, rat. Category 5 Component 540-88-5: LC50: >2.23 mg/l, rat. Category 3

Component 14808-60-7:

Component 64742-95-6:

Component 64742-95-6:

LD50: >5000 mg/kg, rat. Category 5

LD50: >5000 mg/kg, rat. Category 5

Respiratory/Skin Sensitization: Component 100-41-4: No evidence of respiratory or skin sensitization.

Randolph Products Company

MIL-PRF-85285E 24052 TYPE 1 AND 2 CLASS H - POLYURETHANE TOPCOAT TWO COMPONENT TOUCH-UP PEN Date Printed: 11/6/2019

Page 10 of 18

No evidence of respiratory or skin sensitization.

Component 78-93-3:

No evidence of respiratory or skin sensitization.

Component 540-88-5:

No evidence of respiratory or skin sensitization.

Carcinogenicity:

Component 100-41-4:

Not listed as a carcinogen by IARC, NTP, OSHA or ACGIH

Component 1333-86-4:

Listed by IARC as a group 2B carcinogen (possibly carcinogenic to humans).

Carbon Black is not listed as a carcinogen by

NTP, OSHA or ACGIH. GHS Category 2.

Component 13463-67-7:

Listed by IARC as a group 2B carcinogen (possibly carcinogenic to humans). GHS Category 2.

Component 14808-60-7:

Listed by IARC as a group 1 carcinogen (carcinogenic to humans), and as a known carcinogen by NTP. GHS Category 1A.

Component 64742-95-6:

Not listed as a carcinogen by IARC, NTP, OSHA or ACGIH

Component 78-93-3:

Not listed as a carcinogen by IARC, NTP, OSHA or ACGIH.

Component 540-88-5:

Not listed as a carcinogen by IARC, NTP, OSHA or ACGIH.

Reproductive Toxicity:

Component 100-41-4:

No evidence of human reproductive toxicity.

Component 64742-95-6:

SAFETY DATA SHEET Randolph Products Company MIL-PRF-85285E 24052 TYPE 1 AND 2 CLASS H - POLYURETHANE TOPCOAT TWO COMPONENT TOUCH-UP PEN Date Printed: 11/6/2019 Page 11 of 18 No evidence of human reproductive toxicity. Component 78-93-3: No evidence of human reproductive toxicity. Component 540-88-5: No evidence of human reproductive toxicity. Germ Cell Mutagenicity: Component 100-41-4: No data Component 64742-95-6: No data Component 78-93-3: No data Component 540-88-5: No data Aspiration Toxicity: Component 100-41-4: Not classified as an Aspiration Hazard. Component 64742-95-6:

Aspiration Hazard; Category 1

Component 108-10-1: Aspiration Hazard; Category 1 Component 78-93-3: Not classified as an Aspiration Hazard. Component 123-86-4: Not classified as an Aspiration Hazard. Component 540-88-5: Not classified as an Aspiration Hazard.

Component 108-65-6: Not classified as an Aspiration Hazard.

STOT-single exposure

Randolph Products Company

```
MIL-PRF-85285E 24052 TYPE 1 AND 2 CLASS H - POLYURETHANE TOPCOAT TWO COMPONENT TOUCH-UP PEN
Date Printed: 11/6/2019
Page 12 of 18
Component 100-41-4:
No data
Component 64742-95-6:
No data
Component 108-10-1:
No data Component 78-93-3:
No data
Component 123-86-4:
No data Component 540-88-5:
Transient target organ effects (Category 3);
Respiratory tract irritation.
Component 108-65-6:
No data
STOT-repeated exposure
Component 100-41-4:
Repeated exposure affected liver, kidneys
Component 64742-95-6:
Repeated exposure affected kidneys, blood, adrenal gland.
Component 108-10-1:
No data Component 78-93-3:
No data
Component 123-86-4:
No data
Component 540-88-5:
No data
Component 108-65-6:
No data
Routes of Exposure:
Inhalation of vapors, skin/eye/mucous membrane absorption, ingestion.
```

12. Ecological Information

```
Environmental Toxicity:
Component 100-41-4:
LC50: <10 mg/l (fish); EC50: <10 mg/l (daphnia); EC50: <10 mg/l (algae); EC50: <10 mg/l (bacteria)</pre>
```

Randolph Products Company

MIL-PRF-85285E 24052 TYPE 1 AND 2 CLASS H - POLYURETHANE TOPCOAT TWO COMPONENT TOUCH-UP PEN Date Printed: 11/6/2019 Page 13 of 18 Component 1333-86-4: LC50: <1000 mg/l (fish); EC50: <5600 mg/l (daphnia); EC50: <10,000 mg/l (algae) Component 64742-95-6: LC50: 10 mg/l (fish); EC50: 4.5 mg/l (daphnia); EC50: 3.1 mg/l (algae) Component 108-10-1: LC50: 505 mg/l (fish); EC50: 1000 mg/l (daphnia); EC50: 980 mg/l (algae) Component 78-93-3: LC50: 2993 mg/l (fish); EC50: 308 mg/l (daphnia); EC50: 2029 mg/l (algae) Component 123-86-4: LC50: 100 mg/l (fish); EC50: 72.8-205 mg/l (daphnia) Component 540-88-5: Low toxicity: fish, daphnia; EC50: 16 mg/l (algae); EC50: 1.5 mg/l (bacteria) Component 108-65-6: LC50: 161 mg/l (fish); EC50: 373 mg/l (daphnia); EC50: >1000 mg/l (algae) Persistance & degradability: Component 100-41-4: Readily biodegradable Component 1333-86-4: Carbon Black is essentially elemental carbon & cannot be further biodegraded by microorganisms. Component 64742-95-6: Readily biodegradable Component 108-10-1: Readily biodegradable Component 78-93-3: Readily biodegradable Component 123-86-4: No Data Component 540-88-5: Inherently biodegradable Component 108-65-6: Readily biodegradable Bioaccumulative potential: Component 100-41-4: Does not bioaccumulate Component 1333-86-4: Not expected to bioaccumulate. Component 64742-95-6: No Data

Component 108-10-1:

Randolph Products Company

MIL-PRF-85285E 24052 TYPE 1 AND 2 CLASS H - POLYURETHANE TOPCOAT TWO COMPONENT TOUCH-UP PEN Date Printed: 11/6/2019 Page 14 of 18 No Data Component 78-93-3: No Data Component 123-86-4: No Data Component 540-88-5: Not expected to bioaccumulate Component 108-65-6: No Data Mobility in soil: Component 100-41-4: Mobile; may contaminate groundwater Component 64742-95-6: No data Component 108-10-1: No data Component 78-93-3: No data

Component 123-86-4: No data

Randolph Products Company

MIL-PRF-85285E	24052	TYPE	1	AND	2	CLASS	Н	-	POLYURETHANE	TOPCOAT	TWO	COMPONENT	TOUCH-UP	PEN
Date Printed: 1	11/6/20	19												

Page 15 of 18

Component 540-88-5:
No data

Component 108-65-6:
No data

Other Adverse Ecological Effects: Component 100-41-4: Dissolved material evaporates rapidly - within a day from water or soil surfaces.

Component 64742-95-6:
Toxic to aquatic life with long lasting results.

Component 540-88-5: Harmful to aquatic life.

Randolph Products Company

MIL-PRF-85285E 24052 TYPE 1 AND 2 CLASS H - POLYURETHANE TOPCOAT TWO COMPONENT TOUCH-UP PEN

Date Printed: 11/6/2019

Page 16 of 18

13. Disposal Considerations

Waste Disposal Method:

Discharge, treatment or disposal is subject to national, state, or local laws.

When a decision is made to discard this

material as supplied, it meets RCRA's characteristic definition of ignitability.

The toxicity characteristic (TC) has

not been evaluated by the Toxicity Characteristic Leaching Procedure (TCLP).

Federal Regulations may apply to empty container. State and/or local

regulations may be different.

Of the methods of disposal currently available, it is recommended that an

alternative be selected according to the

following order of preference, based upon environmental acceptability: (1)

recycle or rework, if feasible; (2)

incinerate at an authorized facility; or (3) treat at an acceptable waste

treatment facility.

Be sure to contact the appropriate government environmental agencies if further quidance is required.

14. Transport Information

Domestic (Land, DOT), International (Water, IMO/IMDG), International (Air, ICAO)

Road and Rail (ADR/RID), Air (ICAO/IATA), Vessel (IMO/IMDG):

DOT (USA) Shipping Name: Paint

UN/NA ID No: UN1263

Hazard Class: Class 3 (IATA/49CFR)

Packing Group: II

Environmental Hazards:

INFORMATION NOT AVAILABLE.

Marine Pollutant:

Components of this product do not appear on the list of Marine Pollutants (49CFR 172.101)

Special Precautions for User:

INFORMATION NOT AVAILABLE.

15. Regulatory Information

Randolph Products Company

MIL-PRF-85285E 24052 TYPE 1 AND 2 CLASS H - POLYURETHANE TOPCOAT TWO COMPONENT TOUCH-UP PEN Date Printed: 11/6/2019

Page 17 of 18

U.S. Federal Regulations:

TSCA: All components of this material are on the US TSCA 8(b) Inventory or are exempt from listing.

OSHA:

This product is hazardous under OSHA's Hazard Communication Std. Not regarded as a health hazard under current legislation.

CERCLA: SARA Hazard Category:

INFORMATION NOT AVAILABLE.

Section 313:

"*" Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.

International Regulations:

Canadian WHMIS:

INFORMATION NOT AVAILABLE.

Canadian Environmental Protection Act (CEPA):

INFORMATION NOT AVAILABLE.

EINECS:

INFORMATION NOT AVAILABLE.

State Regulations:

"#" Indicates a chemical known to the state of California to cause cancer, birth defects or other reproductive harm.

"+" Indicates a Clean Air Act Hazardous Air Pollutant (HAP).

Volatile Organic Compounds:

COATING VOC content is being expressed as mass of VOC per unit volume of coating less water and exempt solvents, where

applicable.

MATERIAL VOC content is the actual weight of VOC per unit volume.

16. Other Information

Date Revised: 10/04/18

Prepared By: Regulatory Compliance

Information Contact: Regulatory Compliance 413-592-4191 ext 106

Manufacturer Disclaimer:

USERS RESPONSIBILITY: A bulletin such as this cannot be expected to cover all possible individual situations. As the

user has the responsibility to provide a safe workplace, all aspects of an individual operation should be examined to

determine if, or where, precautions - in addition to those described herein - are required. Any health hazard and

safety information herein should be passed on to your customers or employees, as the case may be.

DISCLAIMER OF LIABILITY: The information contained herein is, to the best of our knowledge and belief, accurate.

Randolph Products Company

MIL-PRF-85285E 24052 TYPE 1 AND 2 CLASS H - POLYURETHANE TOPCOAT TWO COMPONENT TOUCH-UP PEN Date Printed: 11/6/2019

Page 18 of 18

However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by use of this material. All chemicals may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot quarantee that these are the only hazards which exist. Final determination of suitability of the chemical is the sole responsibility of the user. No representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose or any other nature are made hereunder with respect to the information contained herein or the chemical to which the information refers. These data relate only to the specific material designated herein and do not relate to use in

combination with any other material. It is the responsibility of the user to comply with all applicable federal, state and local laws and regulations.

End of Material Safety Data Sheet