Randolph Products Company

MIL-PRF-85285E 10000 TYPE 1 AND 2 CLASS H - POLYURETHANE TOPCOAT TWO COMPONENT TOUCH-UP PEN

Date Printed: 9/18/2019

Page 1 of 11

1. Product and Company Identification

Product Name: MIL-PRF-85285E 10000 TYPE 1 AND 2 CLASS H-POLYURETHANE TOPCOAT TWO COMPONENT TOUCH-UP PEN

Product Code: 8010-01-441-6017 p/n 801085285 (Part A, color 10000-clear) Recommended Use: Please refer to Product Information/Technical Data Sheet.

Company Identification:

Randolph Products Company 33 Haynes Circle Chicopee, MA 01020

Information Phone: 413-592-4191

Emergency Phone: ChemTel 800-255-3924

Product filled by:
Delaware Paint Company
8455 Rausch Drive
Plain City, Ohio 43064
740-368-9981

2. Hazards Identification

EMERGENCY OVERVIEW

HAZARD CLASSIFICATION:

FLAMMABLE LIQUID, CATEGORY 2

ACUTE TOXICITY (ORAL), CATEGORY 4

SKIN IRRITATION, CATEGORY 2

EYE IRRITATION, CATEGORY 2B

SPECIFIC TARGET ORGAN TOXICITY-SINGLE EXPOSURE, CATEGORY 3 (CENTRAL NERVOUS SYSTEM)

SYSTEM)

SIGNAL WORD: DANGER







HAZARD STATEMENTS:

Randolph Products Company

MIL-PRF-85285E 10000 TYPE 1 AND 2 CLASS H - POLYURETHANE TOPCOAT TWO COMPONENT TOUCH-UP PEN Date Printed: 9/18/2019 Page 2 of 11 HIGHLY FLAMMABLE LIQUID AND VAPOR HARMFUL IF SWALLOWED CAUSES SKIN IRRITATION CAUSES EYE TRRITATION PRECAUTIONARY STATEMENTS: Keep away from heat, sparks, open flame/hot surfaces. No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting and other equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Store in a well ventilated place. Keep cool. Store locked up. Wash hands thoroughly after handling. Do not eat or drink while using this product. If swallowed, immediately call a poison control center. Rinse mouth. Wear protective gloves, protective clothing, eye/face protection. If on skin, wash with plenty of water. If skin irritation occurs, seek medical advice. Take off contaminated clothing and wash it before reuse. If in eyes, rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: get medical attention. Potential Health Effects Eve: Can cause eye irritation. Causes skin irritation. If swallowed, call a poison control center or physician if you feel unwell. Rinse mouth. Inhalation: May cause drowsiness or dizziness. Chronic (Cancer) Information: IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probably, possible or confirmed human carcinogen by IARC. ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

OSHA: No component of this product present at levels greater than or equal to

0.1% is identified as a carcinogen or

Randolph Products Company

MIL-PRF-85285E 10000 TYPE 1 AND 2 CLASS H - POLYURETHANE TOPCOAT TWO COMPONENT TOUCH-UP PEN Date Printed: 9/18/2019

Page 3 of 11

potential carcinogen by OSHA.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Teratology (Birth Defects) Information:

No specific information.

Reproduction Information:

No specific information.

Aggravation of Pre-Existing Conditions:

Dermititis or other skin conditions.

3. Composition/Information on Ingredients

| Component | CAS# | % by Wt. |
|--|----------|----------|
| PROPYLENE GLYCOL MONOMETHYL ETHER ACETATE SUPPLIER RECOMMENDED: 30 PPM TWA | 108-65-6 | 17 |
| METHYL NORMAL AMYL KETONE | 110-43-0 | 17 |
| OSHA PEL 100 PPM - TWA | | |
| OSHA VPEL 100 PPM -TWA | | |
| ACGIH TLV 50 PPM - TWA | | |
| ACGIH TLV 233 MG/M3 - TWA N-BUTYL ACETATE | 123-86-4 | 6 |
| ACGIH: 150 PPM TWA | 123-00-4 | 0 |
| OSHA: 150 PPM TWA | | |
| ACGIH: 200 PPM STEL | | |
| OSHA: 200 PPM CEILING | | |
| 2,4-PENTANEDIONE | 123-54-6 | 2 |
| EXPOSURE LIMITS: NOT ESTABLISHED | | |
| METHYL ETHYL KETONE | 78-93-3 | 1 |
| ACGIH: 200 PPM TWA | | |
| OSHA: 200 PPM TWA | | |
| | | |

4. First Aid Measures

Eyes:

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

Skin:

If on skin: wash with plenty of soap & water. If skin irritation occurs: Get Medical advice/attention.

Take off contaminated clothing and wash it before reuse.

Randolph Products Company

MIL-PRF-85285E 10000 TYPE 1 AND 2 CLASS H - POLYURETHANE TOPCOAT TWO COMPONENT TOUCH-UP PEN

Date Printed: 9/18/2019

Page 4 of 11

Ingestion:

If swallowed: Immediately call a poison center/physician.

Do NOT induce vomiting.

Inhalation:

If symptomatic, move to fresh air. Get medical attention if symptoms persist.

Note to Physicians:

INFORMATION NOT AVAILABLE.

5. Fire Fighting Measures

Flammable Properties:

Flash Point: 20 F Method:

Explosive Limits:

Lower explosive limit: 1.1 Upper explosive limit: 11.4

Autoignition Temperature:

INFORMATION NOT AVAILABLE.

Hazardous Combustion Products:

Smoke, soot and carbon dioxide, carbon monoxide.

Extinguishing Media:

Dry chemical, CO2, Halon, Foam

Firefighting Procedures:

Special Fire-Fighting Procedures: Wear self-contained breathing apparatus and protective clothing.

Unusual Fire and Explosion Hazards: High temperatures can cause sealed

containers to rupture due to a build up of

internal pressure. Cool with water spray. Vapors are heavier than air and can travel some distance away and flash back.

Sensitivity to Static Discharge: Material may accumulate a static charge which could act as an ignition source.

Precautions should be taken when pouring to minimize splash/free fall.

6. Accidental Release Measures

Small Spill:

See Information for Large Spill, below:

Large Spill:

Use personal protective equipment. Ensure adequate ventilation. Remove all

sources of ignition. Evacuate personnel to

safe areas. Beware of vapors accumulating to form explosive concentrations.

Vapors can accumulate in low areas.

Environmental Precautions:

Methods/Materials for Containment and Cleaning Up:

Randolph Products Company

MIL-PRF-85285E 10000 TYPE 1 AND 2 CLASS H - POLYURETHANE TOPCOAT TWO COMPONENT TOUCH-UP PEN Date Printed: 9/18/2019

Page 5 of 11

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand earth, diatomaceous earth, vermiculite) and place in container for disposal according to local/state/federal regulations.

7. Handling and Storage

Handling:

Keep away from heat, sparks, open flames, hot surfaces. NO SMOKING. Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/processing equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Wear protective gloves/eye protection/face protection.

Storage:

INFORMATION NOT AVAILABLE.

8. Exposure Controls/Personal Protection

Airborne Exposure Limits:

SEE SECTION 3 FOR THIS INFORMATION

Engineering Controls:

Ventilation: Good general ventilation (typically 10 air changes per hour) should be used.

Ventilation rates should be matched to conditions.

Ventilation should be explosion proof.

Supplementary local exhaust ventilation, closed systems, or respiratory protection may be needed in special

circumstances such as poorly ventilated spaces, spray painting, mechanical generation of dusts, heating, drying, etc.

Personal Protective Equipment

Respiratory Protection:

If engineering controls do not maintain airborne concentrations to an acceptable level, an approved respirator must be

worn. In the United States of America, if respirators are used, a program should be instituted to assure compliance

with OSHA Standard 63 CFR 1152, January 8, 1998. Respirator type: Organic Vapor.

Skin Protection:

Wear impervious gloves to prevent skin contact.

Recommended Decontamination Facilities: eye bath, washing facilities, safety shower.

Randolph Products Company

MIL-PRF-85285E 10000 TYPE 1 AND 2 CLASS H - POLYURETHANE TOPCOAT TWO COMPONENT TOUCH-UP PEN

Date Printed: 9/18/2019

Page 6 of 11

Eye Protection:

Chemical safety goggles or glasses with side shields.

9. Physical and Chemical Properties

Boiling Point: 175 F

Melting Point:

INFORMATION NOT AVAILABLE.

Freezing Point: n/a

Vapor Pressure:

INFORMATION NOT AVAILABLE.

Vapor Density: HEAVIER THAN AIR

Solubility in Water:

NEGLIGIBLE

Evaporation Rate: SLOWER THAN ETHER

Specific Gravity: 1.026

Weight per Gallon: 8.541 lb/gl

Coating VOC: 3.75 lb/gl

Material VOC: 3.75 lb/gl

Odor:

Mild solvent odor.

Appearance:

Liquid.

Partition Coefficient:

INFORMATION NOT AVAILABLE.

10. Stability and Reactivity

Chemical Stability (Conditions to Avoid):

Stable under normal storage/use conditions.

Incompatibility:

Avoid strong oxidizing agents, acids and alkalies.

Hazardous Decomposition Products:

INFORMATION NOT AVAILABLE.

Hazardous Polymerization:

Will not occur under normal conditions.

11. Toxicological Information

Eye Irritation/Damage:

Component 78-93-3:

Mild eye irritation, Category 2B

Randolph Products Company

MIL-PRF-85285E 10000 TYPE 1 AND 2 CLASS H - POLYURETHANE TOPCOAT TWO COMPONENT TOUCH-UP PEN Date Printed: 9/18/2019

Page 7 of 11

No data

Skin Irritation/Damage:

```
Component 78-93-3:
Moderate skin irritation, Category 2
LD50: >5000 mg/kg, rabbit
Acute Oral Toxicity:
Component 78-93-3:
LD50: 2300-3500 mg/kg, rat. Category 5
Component 123-86-4:
LD50: 10,700 mg/kg, rat. Category 5
Component 108-65-6:
LD50: no data
Acute Inhalation Toxicity:
Component 78-93-3:
LD50: 11,700 mg/kg, rat. Category 5
Respiratory/Skin Sensitization:
Component 78-93-3:
No evidence of respiratory or skin sensitization.
Carcinogenicity:
Component 78-93-3:
Not listed as a carcinogen by IARC, NTP, OSHA or ACGIH.
Reproductive Toxicity:
Component 78-93-3:
No evidence of human reproductive toxicity.
Germ Cell Mutagenicity:
Component 78-93-3:
No data
Aspiration Toxicity:
Component 78-93-3:
Not classified as an Aspiration Hazard.
Component 123-86-4:
Not classified as an Aspiration Hazard.
Component 108-65-6:
Not classified as an Aspiration Hazard.
STOT-single exposure
Component 78-93-3:
```

Randolph Products Company

```
MIL-PRF-85285E 10000 TYPE 1 AND 2 CLASS H - POLYURETHANE TOPCOAT TWO COMPONENT TOUCH-UP PEN
Date Printed: 9/18/2019
Page 8 of 11
Component 123-86-4:
No data Component 108-65-6:
No data
STOT-repeated exposure
Component 78-93-3:
No data
Component 123-86-4:
No data
Component 108-65-6:
No data
Routes of Exposure:
Inhalation of vapors, skin/eye/mucous membrane absorption, ingestion.
12. Ecological Information
Environmental Toxicity:
Component 78-93-3:
LC50: 2993 mg/l (fish); EC50: 308 mg/l (daphnia); EC50: 2029 mg/l (algae)
Component 123-86-4:
LC50: 100 mg/l (fish); EC50: 72.8-205 mg/l (daphnia)
Component 108-65-6:
LC50: 161 mg/l (fish); EC50: 373 mg/l (daphnia); EC50: >1000 mg/l (algae)
Persistance & degradability:
Component 78-93-3:
Readily biodegradable
Component 123-86-4:
No Data
Component 108-65-6:
Readily biodegradable
Bioaccumulative potential:
Component 78-93-3:
No Data
Component 123-86-4:
No Data
Component 108-65-6:
No Data
```

Mobility in soil: Component 78-93-3:

Randolph Products Company

MIL-PRF-85285E 10000 TYPE 1 AND 2 CLASS H - POLYURETHANE TOPCOAT TWO COMPONENT TOUCH-UP PEN Date Printed: 9/18/2019

Page 9 of 11

No data

Component 123-86-4: No data

Component 108-65-6: No data

Other Adverse Ecological Effects: No information

13. Disposal Considerations

Waste Disposal Method:

Discharge, treatment or disposal is subject to national, state, or local laws. When a decision is made to discard this

material as supplied, it meets RCRA's characteristic definition of ignitability. The toxicity characteristic (TC) has

not been evaluated by the Toxicity Characteristic Leaching Procedure (TCLP).

Federal Regulations may apply to empty container. State and/or local regulations may be different.

Of the methods of disposal currently available, it is recommended that an alternative be selected according to the

following order of preference, based upon environmental acceptability: (1) recycle or rework, if feasible; (2)

incinerate at an authorized facility; or (3) treat at an acceptable waste treatment facility.

Randolph Products Company

MIL-PRF-85285E 10000 TYPE 1 AND 2 CLASS H - POLYURETHANE TOPCOAT TWO COMPONENT TOUCH-UP PEN Date Printed: 9/18/2019

Page 10 of 11

Be sure to contact the appropriate government environmental agencies if further guidance is required.

14. Transport Information

Domestic (Land, DOT), International (Water, IMO/IMDG), International (Air, ICAO)

Road and Rail (ADR/RID), Air (ICAO/IATA), Vessel (IMO/IMDG):

DOT (USA) Shipping Name: Paint Related Material

UN/NA ID No: UN1263

Hazard Class: Class 3 (IATA/49CFR)

Packing Group: II

Environmental Hazards:

INFORMATION NOT AVAILABLE.

Marine Pollutant:

Components of this product do not appear on the list of Marine Pollutants (49CFR 172.101)

Special Precautions for User:

INFORMATION NOT AVAILABLE.

15. Regulatory Information

U.S. Federal Regulations:

TSCA: All components of this material are on the US TSCA 8(b) Inventory or are exempt from listing.

OSHA:

This product is hazardous under OSHA's Hazard Communication Std. Not regarded as a health hazard under current legislation.

CERCLA: SARA Hazard Category:

INFORMATION NOT AVAILABLE.

Section 313:

"*" Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.

International Regulations:

Canadian WHMIS:

INFORMATION NOT AVAILABLE.

Canadian Environmental Protection Act (CEPA):

INFORMATION NOT AVAILABLE.

EINECS:

INFORMATION NOT AVAILABLE.

State Regulations:

INFORMATION NOT AVAILABLE.

Volatile Organic Compounds:

COATING VOC content is being expressed as mass of VOC per unit volume of coating less water and exempt solvents, where

Randolph Products Company

MIL-PRF-85285E 10000 TYPE 1 AND 2 CLASS H - POLYURETHANE TOPCOAT TWO COMPONENT TOUCH-UP PEN Date Printed: 9/18/2019

Page 11 of 11

applicable.

MATERIAL VOC content is the actual weight of VOC per unit volume.

16. Other Information

Date Revised: 01/11/19

Prepared By: Regulatory Compliance

Information Contact: Regulatory Compliance 413-592-4191 ext 106

Manufacturer Disclaimer:

USERS RESPONSIBILITY: A bulletin such as this cannot be expected to cover all possible individual situations. As the

user has the responsibility to provide a safe workplace, all aspects of an individual operation should be examined to

determine if, or where, precautions - in addition to those described herein - are required. Any health hazard and

safety information herein should be passed on to your customers or employees, as the case may be.

DISCLAIMER OF LIABILITY: The information contained herein is, to the best of our knowledge and belief, accurate.

However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no

liability for damages incurred by use of this material. All chemicals may present unknown health hazards and should be

used with caution. Although certain hazards are described herein, we cannot quarantee that these are the only hazards

which exist. Final determination of suitability of the chemical is the sole responsibility of the user. No

representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose or any

other nature are made hereunder with respect to the information contained herein or the chemical to which the

information refers. These data relate only to the specific material designated herein and do not relate to use in

combination with any other material. It is the responsibility of the user to comply with all applicable federal, state and local laws and regulations.

End of Material Safety Data Sheet