## Randolph Products Company

MIL-PRF-85285E 11136 TYPE 1 AND 2 CLASS H - POLYURETHANE TOPCOAT TWO COMPONENT(20Z KIT) Part A

Date Printed: 6/2/2020

Page 1 of 14

### 1. Product and Company Identification

Product Name: MIL-PRF-85285E 11136 TYPE 1 AND 2 CLASS H - POLYURETHANE TOPCOAT TWO COMPONENT(20Z KIT) Part A

Product Code: 8010-01-495-3820 (Part A, color 11136)

Recommended Use: Please refer to Product Information/Technical Data Sheet.

Company Identification:

Randolph Products Company 33 Haynes Circle Chicopee, MA 01020

Information Phone: 413-592-4191

Emergency Phone: ChemTel 800-255-3924

Product filled by:
Delaware Paint Company
8455 Rausch Drive
Plain City, Ohio 43064
740-368-9981

### 2. Hazards Identification

EMERGENCY OVERVIEW

HAZARD CLASSIFICATION:

HIGHLY FLAMMABLE LIQUID & VAPOR, CATEGORY 2

ACUTE TOXICITY (ORAL), CATEGORY 4

SKIN IRRITATION, CATEGORY 2

EYE IRRITATION, CATEGORY 2B

SPECIFIC TARGET ORGAN TOXICITY-SINGLE EXPOSURE, CATEGORY 3 (CENTRAL NERVOUS

SYSTEM)

ASPIRATION HAZARD, CATEGORY 1

CARCINOGENICITY, CATEGORY 2

SIGNAL WORD:

DANGER







## Randolph Products Company

MIL-PRF-85285E 11136 TYPE 1 AND 2 CLASS H - POLYURETHANE TOPCOAT TWO COMPONENT(20Z KIT) Part A

Date Printed: 6/2/2020

Page 2 of 14

#### HAZARD STATEMENTS:

HIGHLY FLAMMABLE LIQUID AND VAPOR

HARMFUL IF SWALLOWED

CAUSES SKIN IRRITATION

CAUSES EYE IRRITATION

MAY CAUSE DROWSINESS OR DIZZINESS

MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS

SUSPECTED OF CAUSING CANCER

#### PRECAUTIONARY STATEMENTS:

Keep away from heat, sparks, open flame/hot surfaces.

No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting and other equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Store/Use outdoors or in a well ventilated place.

Keep cool.

Store locked up.

Wash hands thoroughly after handling.

Do not eat or drink while using this product.

Do not breathe vapors.

If inhaled: Remove person to fresh air and keep comfortable for breathing.

If swallowed, immediately call a poison control center.

Rinse mouth.

Wear protective gloves, protective clothing, eye/face protection.

If on skin or hair: Take off immediately all contaminated clothing. Rinse skin with water/shower.

If skin irritation occurs, seek medical advice.

Take off contaminated clothing and wash it before reuse.

If exposed or concerned, get medical advice or attention.

Call a poison center or doctor if you feel unwell.

If in eyes, rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: get medical attention.

In case of fire: Use dry chemical, CO@, Halon or foam to extinguish.

Dispose of contents/container in accordance with all local, regional, national regulations.

Do NOT induce vomiting.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

#### Potential Health Effects

Eye:

Can cause eye irritation.

Skin:

Causes skin irritation.

## Randolph Products Company

MIL-PRF-85285E 11136 TYPE 1 AND 2 CLASS H - POLYURETHANE TOPCOAT TWO COMPONENT(20Z KIT) Part A Date Printed: 6/2/2020

### Page 3 of 14

#### Ingestion:

If swallowed, call a poison control center or physician if you feel unwell. Rinse mouth.

#### Inhalation:

May cause drowsiness or dizziness.

Chronic (Cancer) Information:

IARC: A component of this product present at levels greater than or equal to 0.1% is identified as a probable, possible or confirmed human carcinogen by IARC.

ACGIH: No component of this product present at leveles greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

OSHA: No component of this product present at leveles greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

NTP: No component of this product present at leveles greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Teratology (Birth Defects) Information:

INFORMATION NOT AVAILABLE.

Reproduction Information:

INFORMATION NOT AVAILABLE.

Aggravation of Pre-Existing Conditions:

Dermititis or other skin conditions.

### 3. Composition/Information on Ingredients

Component	CAS#	% by Wt.
PROPYLENE GLYCOL MONOMETHYL ETHER ACETATE SUPPLIER RECOMMENDED: 30 PPM TWA	108-65-6	19
METHYL NORMAL AMYL KETONE OSHA PEL 100 PPM - TWA	110-43-0	13
OSHA VPEL 100 PPM -TWA ACGIH TLV 50 PPM - TWA		
ACGIH TLV 33 MG/M3 - TWA N-BUTYL ACETATE	123-86-4	4
ACGIH: 150 PPM TWA	123-00-4	4
OSHA: 150 PPM TWA ACGIH: 200 PPM STEL		
OSHA: 200 PPM CEILING SOLVENT NAPHTHA (PETROLEUM), LIGHT AROMATIC OSHA PEL: 500 PPM (2000 MG/M3)	64742-95-6	4
ACGIH TLV: 200 MG/M3 (AS TOTAL HYDROCARBON VAPOR) TERTIARY BUTYL ACETATE	540-88-5	2

## Randolph Products Company

MIL-PRF-85285E 11136 TYPE 1 AND 2 CLASS H - POLYURETHANE TOPCOAT TWO COMPONENT(20Z KIT) Part A

Date Printed: 6/2/2020

Page 4 of 14

ACGIH: 200 PPM TWA OSHA: 200 PPM TWA

IRON OXIDE, RED 1332-37-2 2

ACGIH: 10 MG/M3 TWA (NUISANCE DUST) OSHA: 15 MG/M3 TWA (NUISANCE DUST)

2,4-PENTANEDIONE 123-54-6 2

EXPOSURE LIMITS: NOT ESTABLISHED

# TITANIUM DIOXIDE 13463-67-7 .312

ACGIH: 10 MG/M3 TWA - NUISANCE DUST OSHA: 10 MG/M3 TWA - NUISANCE DUST

#### 4. First Aid Measures

#### Eyes:

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue

rinsing.

If eye irritation persists: Get medical advice/attention.

#### Skin:

If on skin: wash with plenty of soap & water. If skin irritation occurs: Get Medical advice/attention.

Take off contaminated clothing and wash it before reuse.

### Ingestion:

If swallowed: Immediately call a poison center/physician.

Do NOT induce vomiting.

#### Inhalation:

If inhaled: Remove person to fresh air and keep comfortable for breathing.

Call a poison control center/get medical attention if you feel unwell.

Note to Physicians:

Aspiration hazard - do not induce vomiting

### 5. Fire Fighting Measures

### Flammable Properties:

Flash Point: 62 F Method: CC

Explosive Limits:

Lower explosive limit: 1.0 Upper explosive limit: 11.4

Autoignition Temperature:

INFORMATION NOT AVAILABLE.

Hazardous Combustion Products:

Smoke, soot and carbon dioxide, carbon monoxide.

## Randolph Products Company

MIL-PRF-85285E 11136 TYPE 1 AND 2 CLASS H - POLYURETHANE TOPCOAT TWO COMPONENT(20Z KIT) Part A

Date Printed: 6/2/2020

Page 5 of 14

Extinguishing Media:

Dry chemical, CO2, Halon, Foam

Firefighting Procedures:

Special Fire-Fighting Procedures: Wear self-contained breathing apparatus and

protective clothing.

Unusual Fire and Explosion Hazards: High temperatures can cause sealed

containers to rupture due to a build up of

internal pressure. Cool with water spray. Vapors are heavier than air and can

back.

Sensitivity to Static Discharge: Material may accumulate a static charge which

could act as an ignition source.

Precautions should be taken when pouring to minimize splash/free fall.

#### 6. Accidental Release Measures

Small Spill:

See Information for Large Spill, below:

Large Spill:

Use personal protective equipment. Ensure adequate ventilation. Remove all

sources of ignition. Evacuate personnel to

safe areas. Beware of vapors accumulating to form explosive concentrations.

Vapors can accumulate in low areas.

Environmental Precautions:

INFORMATION NOT AVAILABLE.

Methods/Materials for Containment and Cleaning Up:

Contain spillage, and then collect with non-combustible absorbent material,

(e.g. sand earth, diatomaceous earth,

vermiculite) and place in container for disposal according to

local/state/federal regulations.

#### 7. Handling and Storage

Handling:

Keep away from heat, sparks, open flames, hot surfaces. NO SMOKING. Keep

container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/processing equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Wear protective gloves/eye protection/face protection.

Storage:

Prevent unauthorized access.

Store in a well ventilated place.

Keep container tightly closed.

Keep cool.

## Randolph Products Company

MIL-PRF-85285E 11136 TYPE 1 AND 2 CLASS H - POLYURETHANE TOPCOAT TWO COMPONENT(20Z KIT) Part A

Date Printed: 6/2/2020

Page 6 of 14

### 8. Exposure Controls/Personal Protection

Airborne Exposure Limits:

SEE SECTION 3 FOR THIS INFORMATION

Engineering Controls:

Ventilation: Good general ventilation (typically 10 air changes per hour)

should be used.

Ventilation rates should be matched to conditions.

Ventilation should be explosion proof.

Supplementary local exhaust ventilation, closed systems, or respiratory

protection may be needed in special

circumstances such as poorly ventilated spaces, spray painting, mechanical

generation of dusts, heating, drying, etc.

Personal Protective Equipment

Respiratory Protection:

If engineering controls do not maintain airborne concentrations to an

acceptable level, an approved respirator must be

worn. In the United States of America, if respirators are used, a program should be instituted to assure compliance

with OSHA Standard 63 CFR 1152, January 8, 1998. Respirator type: Organic Vapor.

Skin Protection:

Wear impervious gloves to prevent skin contact.

Recommended Decontamination Facilities: eye bath, washing facilities, safety shower.

Eye Protection:

Chemical safety goggles or glasses with side shields.

### 9. Physical and Chemical Properties

Boiling Point: 208.4 F

Melting Point:

INFORMATION NOT AVAILABLE.

Freezing Point: -63F

Vapor Pressure:

Information not available for mixture

Vapor Density:

HEAVIER THAN AIR

Solubility in Water:

NEGLIGIBLE

Evaporation Rate: SLOWER THAN ETHER

## Randolph Products Company

MIL-PRF-85285E 11136 TYPE 1 AND 2 CLASS H - POLYURETHANE TOPCOAT TWO COMPONENT(20Z KIT) Part A Date Printed: 6/2/2020 Page 7 of 14 Specific Gravity: 1.021 Weight per Gallon: 8.5 lb/gl Coating VOC: 3.79 lb/gl Material VOC: 3.71 lb/gl Odor: Mild solvent odor. Appearance: Liquid. Partition Coefficient: INFORMATION NOT AVAILABLE. 10. Stability and Reactivity Chemical Stability (Conditions to Avoid): Stable under normal storage/use conditions. Incompatibility: Avoid strong oxidizing agents, acids and alkalies. Hazardous Decomposition Products: INFORMATION NOT AVAILABLE. Hazardous Polymerization: Will not occur under normal conditions. 11. Toxicological Information Eye Irritation/Damage: Component 64742-95-6: Mild eye irritation, Category 2b Component 540-88-5: Based on available data, the classification criteria are not met. Skin Irritation/Damage: Component 64742-95-6: LD50: >2000 mg/kg, rat. Category 5 Component 540-88-5: LD50: >2000 mg/kg, rabbit. Category 5. Acute Oral Toxicity:

Component 13463-67-7:

Component 64742-95-6:

LD50: 10,000 mg/kg, rat. Category 5

# Randolph Products Company

MIL-PRF-85285E 11136 TYPE 1 AND 2 CLASS H - POLYURETHANE TOPCOAT TWO COMPONENT(20Z KIT) Part A Date Printed: 6/2/2020 Page 8 of 14 LD50: >5000 mg/kg, rat. Category 5 Component 123-86-4: LD50: 10,700 mg/kg, rat. Category 5 Component 540-88-5: LD50: 4,500 mg/kg, rat. Category 5 Component 108-65-6: LD50: no data Acute Inhalation Toxicity: Component 64742-95-6: LC50: 5.6 mg/l, rat. Category 3 Component 540-88-5: LC50: >2.23 mg/l, rat. Category 3 Respiratory/Skin Sensitization: Component 64742-95-6: No evidence of respiratory or skin sensitization. Component 540-88-5: No evidence of respiratory or skin sensitization. Carcinogenicity: Component 13463-67-7: Listed by IARC as a group 2B carcinogen (possibly carcinogenic to humans). GHS Category 2. Component 64742-95-6: Not listed as a carcinogen by IARC, NTP, OSHA or ACGIH Component 540-88-5: Not listed as a carcinogen by IARC, NTP, OSHA or ACGIH.

Reproductive Toxicity: Component 64742-95-6:

# Randolph Products Company

MIL-PRF-85285E 11136 TYPE 1 AND 2 CLASS H - POLYURETHANE TOPCOAT TWO COMPONENT(20Z KIT) Part A Date Printed: 6/2/2020 Page 9 of 14 No evidence of human reproductive toxicity. Component 540-88-5: No evidence of human reproductive toxicity. Germ Cell Mutagenicity: Component 64742-95-6: No data Component 540-88-5: No data Aspiration Toxicity: Component 64742-95-6: Aspiration Hazard; Category 1 Component 123-86-4: Not classified as an Aspiration Hazard. Component 540-88-5: Not classified as an Aspiration Hazard. Component 108-65-6: Not classified as an Aspiration Hazard. STOT-single exposure Component 64742-95-6: No data Component 123-86-4: No data Component 540-88-5: Transient target organ effects (Category 3); Respiratory tract irritation. Component 108-65-6: No data

STOT-repeated exposure Component 64742-95-6:

## Randolph Products Company

```
MIL-PRF-85285E 11136 TYPE 1 AND 2 CLASS H - POLYURETHANE TOPCOAT TWO COMPONENT(20Z KIT) Part A
Date Printed: 6/2/2020
Page 10 of 14
Repeated exposure affected kidneys, blood, adrenal gland.
Component 123-86-4:
No data
Component 540-88-5:
No data
Component 108-65-6:
No data
Routes of Exposure:
Inhalation of vapors, skin/eye/mucous membrane absorption, ingestion.
12. Ecological Information
Environmental Toxicity:
Component 64742-95-6:
LC50: 10 mg/l (fish); EC50: 4.5 mg/l (daphnia); EC50: 3.1 mg/l (algae)
Component 123-86-4:
LC50: 100 mg/l (fish); EC50: 72.8-205 mg/l (daphnia)
Component 540-88-5:
Low toxicity: fish, daphnia; EC50: 16 mg/l (algae); EC50: 1.5 mg/l (bacteria)
Component 108-65-6:
LC50: 161 mg/l (fish); EC50: 373 mg/l (daphnia); EC50: >1000 mg/l (algae)
Persistance & degradability:
Component 64742-95-6:
Readily biodegradable
Component 123-86-4:
No Data
Component 540-88-5:
Inherently biodegradable
Component 108-65-6:
Readily biodegradable
Bioaccumulative potential:
Component 64742-95-6:
No Data
Component 123-86-4:
No Data
Component 540-88-5:
```

Not expected to bioaccumulate

# Randolph Products Company

MIL-PRF-85285	E 11136	TYPE	1 A	ND 2	CLASS	Н	-	POLYURETHANE	TOPCOAT	TWO	COMPONENT (20Z	KIT)	Part	Α
Date Printed:	6/2/202	20												

Page 11 of 14

Component 108-65-6:
No Data

Mobility in soil: Component 64742-95-6: No data Component 123-86-4: No data

Component 540-88-5:
No data

Component 108-65-6: No data

## Randolph Products Company

MIL-PRF-85285E 11136 TYPE 1 AND 2 CLASS H - POLYURETHANE TOPCOAT TWO COMPONENT(20Z KIT) Part A Date Printed: 6/2/2020

Page 12 of 14

Component 64742-95-6:

Toxic to aquatic life with long lasting results.

Component 540-88-5: Harmful to aquatic life.

### 13. Disposal Considerations

Waste Disposal Method:

Discharge, treatment or disposal is subject to national, state, or local laws. When a decision is made to discard this

material as supplied, it meets RCRA's characteristic definition of ignitability.

The toxicity characteristic (TC) has

not been evaluated by the Toxicity Characteristic Leaching Procedure (TCLP).

Federal Regulations may apply to empty container. State and/or local regulations may be different.

Of the methods of disposal currently available, it is recommended that an alternative be selected according to the

following order of preference, based upon environmental acceptability: (1) recycle or rework, if feasible; (2)

incinerate at an authorized facility; or (3) treat at an acceptable waste treatment facility.

Be sure to contact the appropriate government environmental agencies if further guidance is required.

### 14. Transport Information

Domestic (Land, DOT), International (Water, IMO/IMDG), International (Air, ICAO)

Road and Rail (ADR/RID), Air (ICAO/IATA), Vessel (IMO/IMDG):

DOT (USA) Shipping Name: Paint

UN/NA ID No: UN1263

Hazard Class: Class 3 (IATA/49CFR)

Packing Group: II

## Randolph Products Company

MIL-PRF-85285E 11136 TYPE 1 AND 2 CLASS H - POLYURETHANE TOPCOAT TWO COMPONENT(20Z KIT) Part A

Date Printed: 6/2/2020

Page 13 of 14

Environmental Hazards:

INFORMATION NOT AVAILABLE.

Marine Pollutant:

Components of this product do not appear on the list of Marine Pollutants (49CFR 172.101)

Special Precautions for User:

INFORMATION NOT AVAILABLE.

### 15. Regulatory Information

U.S. Federal Regulations:

TSCA: All components of this material are on the US TSCA 8(b) Inventory or are exempt from listing.

OSHA:

This product is hazardous under OSHA's Hazard Communication Std. Not regarded as a health hazard under current legislation.

CERCLA: SARA Hazard Category:

INFORMATION NOT AVAILABLE.

Section 313:

"\*" Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.

International Regulations:

Canadian WHMIS:

INFORMATION NOT AVAILABLE.

Canadian Environmental Protection Act (CEPA):

INFORMATION NOT AVAILABLE.

EINECS:

INFORMATION NOT AVAILABLE.

State Regulations:

"#" Indicates a chemical known to the state of California to cause cancer, birth defects or other reproductive harm.

Volatile Organic Compounds:

COATING VOC content is being expressed as mass of VOC per unit volume of coating less water and exempt solvents, where

applicable.

MATERIAL VOC content is the actual weight of VOC per unit volume.

### 16. Other Information

Date Revised: 01/11/19

Prepared By: Regulatory Compliance

Information Contact: Regulatory Compliance 413-592-4191 ext 106

Manufacturer Disclaimer:

USERS RESPONSIBILITY: A bulletin such as this cannot be expected to cover all

possible individual situations. As the

## Randolph Products Company

MIL-PRF-85285E 11136 TYPE 1 AND 2 CLASS H - POLYURETHANE TOPCOAT TWO COMPONENT(20Z KIT) Part A Date Printed: 6/2/2020

### Page 14 of 14

user has the responsibility to provide a safe workplace, all aspects of an individual operation should be examined to

determine if, or where, precautions - in addition to those described herein - are required. Any health hazard and

safety information herein should be passed on to your customers or employees, as the case may be.

DISCLAIMER OF LIABILITY: The information contained herein is, to the best of our knowledge and belief, accurate.

However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no

liability for damages incurred by use of this material. All chemicals may present unknown health hazards and should be

used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards

which exist. Final determination of suitability of the chemical is the sole responsibility of the user. No

representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose or any

other nature are made hereunder with respect to the information contained herein or the chemical to which the

information refers. These data relate only to the specific material designated herein and do not relate to use in

combination with any other material. It is the responsibility of the user to comply with all applicable federal, state and local laws and regulations.

End of Material Safety Data Sheet